



MR13 Wearable BT UHF Reader

This is our refined and new generation MR13 wearable Bluetooth UHF reader. Being a compact and portable device, it can be operated together with gloves, wristbands, or lanyards and make your work much more flexible and convenient. With a built-in UHF module, the reader possesses a powerful data-collection and transmission function via a simple Bluetooth connection with Android/iOS devices. Removable battery and fast charging capability enable it to achieve work continuity for a long duration. Besides, this tiny device has the protection features like dustproof, waterproof, shockproof, and drop resistance. All these functions make it a most adaptable device in a wide spectrum of circumstances such as logistics & express delivery, retail store management, warehouse management, power patrol inspection, asset management, e-commerce picking, and tickets checking, etc. helping users free their hands and significantly improve work efficiency.



Specification

Physical Characteristics

Dimensions	50 × 60 × 18 mm / 1.97 × 2.36 × 0.71 in.
Weight	64 g / 2.26 oz. (with glove: 90 g / 3.17 oz.)
Color	Yellow, Blue, Gray
Port	USB Type-C
Button	ON/OFF, SCAN
Battery	1000 mAh (removable)
Charging Current	5 V / 1.5 A
Charging Duration	1 hours
LED Indicator	Red indicator will be ON when charging; Blue indicator will be ON when device has been fully charged; Green indicator will be ON when battery is higher than 20%; Green indicator will flash when battery is lower than 20%; Bluetooth is not paired when bluetooth indicator is OFF; Bluetooth is paired when bluetooth indicator is ON

Performance

MCU	Cortex-M3
------------	-----------

Developing Environment

SDK	Android / IOS SDK Supported
Security	RFID Encrypted Module (reserve)

Communication

USB Type C	USB connection to realize data transfer
BT	Bluetooth 5.0

User Environment

Operating Temp.	-20 °C to +50 °C
Storage Temp.	-40 °C to +70 °C
Humidity	5% RH - 95% RH non condensing
Dropping	1.2 m dropping on concrete
Sealing	IP65

UHF

Antenna parameter	Linear Polarized Antenna
Frequency	920-925 MHz / 902-928 MHz / 865-868 MHz
Protocol	EPC C1 GEN2 / ISO18000-6C
R/W range	80 cm

*Range depends on tags and environment

Accessories (Optional)

Glove, wristband, lanyard

Notice: Product specifications are subject to change without prior notice. / Model: MR13 / Update Date: 2021-05-26

Marson Technology Co.,LTD
6F, NO. 108-1 Min-Chuan Road, Hsin-Tien Dist., New Taipei City 23141, Taiwan R.O.C.
TEL: 02-2218-1633 | FAX: 02-2218-6638 | Email: info@marson.com.tw