



MT110/M Mini Scanner

With built-in Bluetooth® technology, MT110/M mini barcode scanner can send data to the host up to 10 meters away. This pocket-sized lightweight wireless 1D barcode scanner with patented green LED illumination is a dexterous mini companion for healthcare and hygiene-sensitive applications which work on laptops, tablets, smart phones or other mobile devices with iOS®, Android® and Windows®.

Increasing Mobile Productivity

- Mini size (W27.5 x L68.4 x H16.2 mm) and lightweight (27g).
- Supports both audio and haptic feedback.
- 2MB memory supports both on-line and off-line operation.
- Built with medical-grade anti-microbial housing.

Easy and Flexible Operations

- Indicators : Buzzer, LED and Vibrator
- Interfaces : BT HID/ BT SPP/ USB HID/ USB VCP/ Memory



Optic & Performance

Light Source	525nm visible red LED
Sensor	Linear Image Sensor
Scan Rate	650 Scans/Sec
Resolution	4Mil/ 0.1mm
Scan Angle	41°
Pitch / Skew / Roll Angle	±30° / ±40° / ±20°
Print Contrast Ratio	30%
Width of Field	140 mm (13Mil Code39)
Typical D.O.F (@800 lux)	UPC/ EAN 13Mil: 39 ~ 248 mm

Physical Characteristics

Dimension	W27.5 x L68.4 x H16.2 mm
Weight	27g
Color	MT110: Black, MT110M: White
Material	PC
Cable	Mini(M) to USB A(M) Cable, 1.5M
Trigger	Scan Button, Function Button
Indicator	LED, Buzzer, Vibrator

Electrical

Operation Voltage	3.7 VDC ± 5%
Working Current	< 170mA
Standby Current	< 60mA
Power Down Current	< 500uA
Battery	3.7V, 400mAh, Li-Polymer Battery
Number of Scan (per full charge)	5,400 scans (1 scan/ 5 secs, Bluetooth® connected)

Connectivity

Radio	Bluetooth® 5.0
Range	66 ft/ 20M (line of sight)
Interface/ Profile	BT HID, BT SPP, USB HID, USB VCP, Memory

User Environment

Operating Temperature	-20 ~ 50°C
Storage Temperature	-20 ~ 60°C
Humidity	0% ~ 95% RH (Non-condensing)
Drop Durability	1.5M
Ambient Light	100,000 Lux (Sunlight)

Regulatory

ESD	Functional after 4KV contact, 8KV air discharge
EMC/RF	FCC Part 15B Class B, Part15C, CE EN55022/24/32, EN301489-1-17, EN300328 V2.1.1, TELEC
Safety Approval	EN/IEC62471 (Exempt Group), EN/IEC60950-1
Environmental	WEEE, RoHS 2.0

Symbologies

1D	UPC-A/UPC-E, EAN-8/EAN-13, Industrial 2 of 5, Codabar, Matrix 2 of 5, Code 11, Code 93, Code 32, Code 128, Standard Code 39, Full ASCII Code 39, Interleaved 2 of 5, China Postal Code, MSI Plessey Code, UK Plessey Code, EAN/UCC 128, Telepen Code, IATA Code, GS1 Databar
----	--

* All specifications are subject to change without notice.



MARSON TECHNOLOGY CO., LTD.

TEL: +886-2-2218-1633

FAX: +886-2-2218-6638

Web: www.marson.com.tw

