



## MT584 2D Wireless Ring Scanner

With built-in Bluetooth® 5.0 technology, MT584 wireless ring scanner can send data to the host up to 20 meters away. This wearable lightweight wireless 2D barcode scanner enables hands-free scanning for mobile operators who work with laptops, tablets, smart phones or other mobile devices with iOS®, Android® and Windows®.

### Ergonomic Design for Mobile Operators

- The smallest and lightest wireless ring barcode scanner.
- Wearable design enabling hands-free barcode scanning.
- Disinfectant-ready housing improves operational hygiene.
- Ergonomic design with touch-activated scan button.

### Easy and Flexible Operations

- Indicators: LED, Buzzer
- Interfaces: BT HID/BT SPP/USB HID/USB VCP/Memory



Optic & Performance	
Light Source	White LED, Visible red LED
Sensor	640 x 480
Resolution	5mil / 0.125mm (1D), 10mil / 0.25mm (2D)
Scan Angle	Horizontal 37°, Vertical 27.5°
Pitch / Skew / Roll Angle	±60° / ±60° / ±360°
Print Contrast Ratio	25%
Width of Field	141 mm (13Mil Code39)
Memory	2MB (20,000 barcodes)
Typical D.O.F ( @800 lux)	UPC/ EAN 13 Mil: 47 ~ 303 mm
Physical Characteristics	
Dimension	W27.6 x L46.2 x H26.8 mm
Weight	20g
Color	Black or White
Material	PC+ABS
Cable	Micro(M) to USB A(M) Cable, 1.5M
Trigger	Touch Scan Button, Function Button
Indicator	LED, Buzzer
Electrical	
Operation Voltage	3.7 VDC ± 5%
Working Current	< 210mA
Standby Current	< 25mA
Battery	3.7V, 240mAh, Li-Polymer Battery
Number of Scan (per full charge)	4,000 scans (1 scan/ 5 secs, Bluetooth connected)
Connectivity	
Radio	Bluetooth® 5.0 (Class 2)
Range	66 ft/ 20M (line of sight)
Interface/ Profile	BT HID, BT SPP, USB HID, USB VCP, Memory
User Environment	
Operating Temperature	-10 ~ 50°C
Storage Temperature	-20 ~ 60°C
Humidity	0% ~ 95% RH (Non-condensing)
Drop Durability	1.5M
Sealing	IP42
Ambient Light	70,000 Lux (Sunlight)
Regulatory	
ESD	Functional after 4KV contact, 8KV air discharge
EMC/RF	TELEC
Safety Approval	IEC62471 (Exempt Group)
Environmental	WEEE, RoHS 2.0
Symbologies	
1D	UPC-A/ UPC-E0/ UPC-E1, EAN-8/ EAN-13, Code128, Code39, Code93, Codabar, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Standard 2 of 5, China Post 25, Code11, MSI Plessey, Plessey, GS1 Databar, GS1 Databar Limited, GS1 Databar Expanded
2D	QR Code, Micro QR Code, PDF417, MicroPDF417, Data Matrix, Aztec, MaxiCode, Han Xin, Code16K

\* All specifications are subject to change without notice.

