





## **MT8225 Handheld Scanner**

MT8225 is a ergonomic pocket-sized haldheld scanner designedwith a water-proof and dust-proof housing that enables userto operate in the harshest environment. With built-in vibrator, buzzer and LED, MT8225 provides audible, visual and haptic feedback as good read response. The disinfectant-ready housing also prevents the reproduction & spread of bacteria among nurses in hospital.

## **High Efficiency for All Applications**

- Reads all major 2D barcodes in the market.
- Ruggedized design of IP55 and 1.5M drop resistance.
- Anti-microbial housing ensures hygiene among users



## **Easy and Flexible Operations**

• Indicators: Buzzer, LED and Vibrator

• Interfaces: USB HID/ USB VCP





Sensor   1280 x 800
Sensor         1280 x 800           Resolution         3Mil/ 0.075mm           Scan Angle         Horizontal 40°, Vertical 30°           Pitch / Skew / Roll Angle         ±60°/ ±50°/ 360°           Print Contrast Ratio         20%           Width of Field         141 mm (13Mil Code39)           Typical D.O.F (@800 lux)         UPC/EAN 13 Mil : 52 ~ 403 mm QR Code 15 Mil : 37 ~ 235 mm           Physical Characteristics         Dimension           W42.5 x L102 x H21.5 mm           Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Resolution         3Mil/ 0.075mm           Scan Angle         Horizontal 40°, Vertical 30°           Pitch / Skew / Roll Angle         ±60°/ ±50°/ 360°           Print Contrast Ratio         20%           Width of Field         141 mm (13Mil Code39)           Typical D.O.F (@800 lux)         UPC/EAN 13 Mil : 52 ~ 403 mm QR Code 15 Mil : 37 ~ 235 mm           Physical Characteristics           Dimension         W42.5 x L102 x H21.5 mm           Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Scan Angle
Pitch / Skew / Roll Angle         ±60°/ ±50°/ 360°           Print Contrast Ratio         20%           Width of Field         141 mm (13Mil Code39)           Typical D.O.F (@800 lux)         UPC/EAN 13 Mil : 52 ~ 403 mm QR Code 15 Mil : 37 ~ 235 mm           Physical Characteristics           Dimension         W42.5 x L102 x H21.5 mm           Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Print Contrast Ratio         20%           Width of Field         141 mm (13Mil Code39)           Typical D.O.F (@800 lux)         UPC/EAN 13 Mil : 52 ~ 403 mm QR Code 15 Mil : 37 ~ 235 mm           Physical Characteristics           Dimension         W42.5 x L102 x H21.5 mm           Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Width of Field         141 mm (13Mil Code39)           Typical D.O.F (@800 lux)         UPC/EAN 13 Mil : 52 ~ 403 mm QR Code 15 Mil : 37 ~ 235 mm           Physical Characteristics           Dimension         W42.5 x L102 x H21.5 mm           Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Typical D.O.F ( @800 lux)         UPC/EAN 13 Mil : 52 ~ 403 mm QR Code 15 Mil : 37 ~ 235 mm           Physical Characteristics           Dimension         W42.5 x L102 x H21.5 mm           Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
QR Code 15 Mil : 37 ~ 235 mm           Physical Characteristics           Dimension         W42.5 x L102 x H21.5 mm           Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Dimension         W42.5 x L102 x H21.5 mm           Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Weight         89g           Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Color         Black / White           Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Material         PC           Cable         USB A(M) Cable, 1M           Trigger         Scan Button, Function Button           Indicator         LED, Buzzer, Vibrator           Electrical           Operation Voltage         5 VDC ± 5%
Cable USB A(M) Cable, 1M  Trigger Scan Button, Function Button Indicator LED, Buzzer, Vibrator  Electrical  Operation Voltage 5 VDC ± 5%
Trigger Scan Button, Function Button Indicator LED, Buzzer, Vibrator  Electrical  Operation Voltage 5 VDC ± 5%
Indicator         LED, Buzzer, Vibrator           Electrical         Operation Voltage         5 VDC ± 5%
Electrical Operation Voltage 5 VDC ± 5%
Operation Voltage 5 VDC ± 5%
Working Current < 300mA
Standby Current < 70mA
Connectivity
Interface/ Profile USB HID, USB VCP
User Environment
Operating Temperature -20 ~ 50 °C
Storage Temperature -20 ~ 60 °C
Humidity 0% ~ 95% RH (Non-condensing)
Drop Durability 1.5M
Sealing IP55
Ambient Light 70,000Lux (Sunlight)
Regulatory
ESD Functional after 4KV contact, 8KV air discharge
EMC TBA
Safety Approval TBA
Environmental WEEE, RoHS 2.0





TEL:+886-2-2218-1633 FAX: +886-2-2218-6638 Email: info@marson.com.tw



Medical Compliance

(White Version Only)

Symbologies

2D





ISO 22196 (JIS Z 2801), ISO 11737-1/2

UPC-A/ UPC-E, EAN-8/ EAN-13, Code128, GS1-128, Code 39, Code32, Code 93, Code11, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Codabar, MSI, GS1 Databar QR Code, Micro QR Code, Data Matrix, PDF417,





MicroPDF417, Aztec, MaxiCode

\* All specifications are subject to change without notice.