



MT850 Portable Scanner

MT850 is a 2D portable scanner featuring Bluetooth® 5.0 technology, fast and reliable scanning performance, robust, ergonomic design at affordable cost. MT850 can capture all 1D and 2D barcodes from paper surface or mobile display in one-tenth of a second. MT850 2D Portable Scanner delivers high efficiency especially for users who work with iOS® and Android® mobile devices.

High Efficiency for All Applications

- Reads all major 2D barcodes in the market.
- Works in total darkness and direct sunlight
- Waterproof and dust-resistant
- Supports on-line and off-line operation
- Supports Ez Utility configuration utility
- Megapixel sensor enables high density scanning
- High-speed shutter enhances great motion tolerance

Easy and Flexible Operations

- Indicators: Buzzer, LED and Vibrator
- Interfaces: BT HID/ BT SPP/ USB HID/ USB VCP/ Memory
- Compatibility : iOS, Android, Windows



Optic & Performance

Light Source	White LED, visible red LED
Sensor	1280 x 800
Resolution	3Mil / 0.075mm
Scan Angle	Horizontal 40°, Vertical 30°
Pitch / Skew / Roll Angle	±60° / ±50° / 360°
Print Contrast Ratio	20%
Width of Field	141 mm (13Mil Code39)
Memory	2MB (20,000 barcodes)
Typical D.O.F (@800 lux)	UPC/EAN 13 Mil : 45 ~ 285 mm QR Code 15 Mil : 40 ~ 210 mm

Physical Characteristics

Dimension	W42.5 x L102 x H21.5 mm
Weight	71 g
Color	White
Material	PC
Cable	Micro(M) to USB A(M) Cable, 1.5M
Trigger	Scan Button, Function Button
Indicator	LED, Buzzer, Vibrator

Electrical

Operation Voltage	3.7 VDC ± 5%
Working Current	< 330mA
Standby Current	< 60mA
Battery	3.7V, 1000mAh, Li-Polymer Battery
Number of Scan (per full charge)	10,000 scans (1 scan/ 5 secs, Bluetooth connected)

Connectivity

Radio	Bluetooth® 5.0 dual mode (Class 2)
Range	66 ft/ 20M (line of sight)
Interface/ Profile	BT HID, BT SPP, USB HID, USB VCP, Memory

User Environment

Operating Temperature	-10 ~ 50°C
Storage Temperature	-20 ~ 60°C
Humidity	0% ~ 95% RH (Non-condensing)
Drop Durability	1.5M
Sealing	IP55
Ambient Light	70,000 Lux (Sunlight)

Regulatory

ESD	Functional after 4KV contact, 8KV air discharge
EMC/RF	TELEC
Safety Approval	EN/IEC62471 (Exempt Group)
Environmental	WEEE, RoHS 2.0
Medical Compliance	ISO 22196 (JIS Z 2801), ISO 11737-1/2

Symbologies

1D	UPC-A/ UPC-E, EAN-8/ EAN-13, Code128, GS1-128 Code 39, Code32, Code 93, Code11, Interleaved 2 of 5 Matrix 2 of 5, Industrial 2 of 5, Codabar, MSI, GS1 Databar
2D	QR Code, Micro QR Code, Data Matrix, PDF417 MicroPDF417, Aztec, MaxiCode

All specifications are subject to change without notice.



MARSON TECHNOLOGY CO., LTD.

TEL: +886-2-2218-1633

FAX: +886-2-2218-6638

Web: www.marson.com.tw

